



REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2010-06-10

Technical Data

Material:
 Contact Material: Phosphor Bronze
 Contact plating: Au or Sn Over 50μ" Ni
 Insulator Material: Black Polyester UL94V-0
 Standard: PA6T +30%G.F

Electrical:
 Current rating: 3.0Amps/contact max.
 Contact resistance: ≤20mΩ/contact
 Insulation resistance: ≥1000MΩ at V=100V
 Withstanding Voltage: 1000V AC/minute

Mechanical:
 Mechanical life cycle: min.200
 Operating temperatures: Gold Plated: -55°C to +105°C
 Tin plated: -40°C to +105°C
 Soldering temperature: +260°C max (PA6T)

F128	11	XXX	XX	R	X	B	N	A	00
Product Descriptions F128 H=5.0	Product Type 11 Single Row	No. of Positions XXX Poles	Pln Plating G1 Gold 1u" SN Tin Plated	Angle options R Right Angle	Insulator Material A PBT B PA66 C PA6T	Color Black		Series NO. A OC=3.00mm	

ANYCONN® 东莞市恩康电子有限公司
 www.enkcom.com **DONGGUAN ANYCONN ELECTRONICS CO.,LTD**

TOLERANCE	PROJECTON		TITLE: Pitch 2.54 H5.0mm Single Row Right Angle Female Header
ANGLE ±5°	DATE :	2010-06-10	PART NO: F12811XXXXXRCBNA00
X.XXX ±0.10	DRAWN :	Fuqianshan	
X.XX ±0.20	CHECKED :		DRAWING NO: EP-F12811-019
X.X ±0.30	APPROVED :		REV: A0
X. ±0.50			UNIT: mm
			SCALE: 3:1
			SIZE: A4